



PRODUCT DATA SHEET



Product No	5305
Issue No.	2
Issue Date	17/03/10

PRODUCT NAME/VISCOSITIES: DELTAPLEX 2EP

DESCRIPTION:

A lithium complex grease of outstanding performance and a distinctive red in colour.

APPLICATION:

A universal grease suitable for all anti-friction and plain bearings and highly suitable for the lubrication of universal joints.

USER BENEFITS:

- Good mechanical stability and added tenacity.
- Extreme pressure (EP) properties generate excellent load carrying characteristics.
- Good performance over a wide temperature range.
- Excellent resistance to corrosion.

TYPICAL CHARACTERISTICS:

Appearance	Red Smooth Adhesive Grease
NLGI Classification	2
Thickener	Lithium Complex Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	265 to 295
Drop Point (IP132) °C	250 minimum
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	0 : 0
Four Ball Weld Load (IP239)	450kgs
Timken OK Load (IP326)	20kgs (45lbs)
Operating Temperature Range °C	-20 to +150

HEALTH AND SAFETY:

Health and Safety Data Sheet 5305 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

