

PW11 WAXFILM

Page: 1

 Compilation date:
 22/01/2009

 Revision date:
 24/01/2017

Revision No: 1b

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
	PW11 WAXFILM	
Product name. Product code:		
1.2. Relevant identified uses	of the substance or mixture and uses advised against	
Use of substance / mixture:	Rust preventative	
1.3. Details of the supplier of the safety data sheet		
Company name:	Millers Oils Ltd	
	Hillside Oilworks	
	Rastrick Common	
	Brighouse	
	West Yorkshire	
	HD6 3DP	
	United Kingdom	
Tel:	+44 (0)1484 713201	
Fax:	+44 (0)1484 721263	
Email:	<u>h.s@millersoils.co.uk</u>	
1.4. Emergency telephone nu	Imber	
Emergency tel:	+44 (0)1484 713201	
Section 2: Hazards identifica	tion	
2.1. Classification of the sub	stance or mixture	
Classification under CLP:	STOT SE 3: H336; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 3: H226; -:	
	EUH066	
lost important adverse effects:	Repeated exposure may cause skin dryness or cracking. Flammable liquid and vapour.	
	May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.	
	Harmful to aquatic life with long lasting effects.	
2.2. Label elements		
Label elements:		
	EUH066: Repeated exposure may cause skin dryness or cracking.	
המבמות שומוכווושווש.	H226: Flammable liquid and vapour.	

PW11 WAXFILM

 Page: 2

 H304: May be fatal if swallowed and enters airways.

 H336: May cause drowsiness or dizziness.

 H412: Harmful to aquatic life with long lasting effects.

 Signal words:

 Danger

 Hazard pictograms:

 GHS02: Flame

 GHS07: Exclamation mark

 GHS08: Health hazard

 VVV

 VVV

 Precautionary statements:

 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

 P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

 P280: Wear protective gloves/protective clothing/eye protection/face protection.

 P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

 P31: Do NOT induce vomiting.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9-12, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-857-5	-	-	Flam. Liq. 3: H226; STOT SE 3: H336; Asp. Tox. 1: H304; -: EUH066	30-50%

PETROLEUM DISTILLATE - REACH registered number(s): 01-2119484819-18-XXXX

265-150-3	64742-48-9	-	Aquatic Chronic 2: H411; Asp. Tox. 1:	1-10%	
			H304; Flam. Liq. 3: H226; STOT SE 3:		
			H336; Skin Irrit. 2: H315		

Section 4: First aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes.

PW11 WAXFILM

Page: 3

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting. Nausea and stomach pain may occur.

Inhalation: Inhalation of vapours may cause irritation of nose, throat and airway.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: In all cases of doubt, or when symptoms persist, seek medical attention.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

PW11 WAXFILM

Handling requirements:Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.Do not handle in a confined space. Avoid the formation or spread of mists in the air.Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

7.1. Precautions for safe handling

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:If ventilation is insufficient, suitable respiratory protection must be provided.Hand protection:Impermeable gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Beige		
Odour:	Characteristic odour		
Evaporation rate:	Moderate		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Also soluble in:	Most organic solvents.		
Viscosity:	Non-viscous		
Kinematic viscosity:	8 cSt		
Viscosity test method:	Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)		
Boiling point/range°C:	150 - 200 Melting point/range°C:	No data available.	
Flammability limits %: lower:	0.6 upper:	7.0	
Flash point°C:	38 Part.coeff. n-octanol/water:	No data available.	
Autoflammability°C:	> 200 Vapour pressure:	No data available.	
Relative density:	0.845		[cont

PW11 WAXFILM

Page: 5

pH: No data available.

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for substance:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting.

Nausea and stomach pain may occur.

Inhalation: Inhalation of vapours may cause irritation of nose, throat and airway.

Section 12: Ecological information

PW11 WAXFILM

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Expected to be inherently biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile. Insoluble in water. Floats on water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(Contains: Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics.)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

PW11 WAXFILM

Page: 7

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	This safety data sheet is prepared in accordance with Commission Regulation (EC) No
	1272/2008.
	Conforms to regulation (EC) No 1907/2006 (REACH)
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.