



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: PW11 WAX FILM

Product No	5628
Issue No.	2
Issue Date	13/10/09

DESCRIPTION:

Long term protection of ferrous and most non-ferrous components. Wax-film is ideal for protection of vehicle underbodies during storage and warranty period and particularly for application into closed sections and inner panels. Formulated to meet Ministry of Defence Specification PX32 DEF STAN 80-83-3 and BS Type Tp 1c (BS 1133 Section 6).

Excellent on springs, linkages and other components in inaccessible areas when wishing to protect from water and salt corrosion. Ideal during car or commercial restoration work for total protection of unpainted panels. Agricultural equipment can be treated to Wax-film whilst being laid up both indoors and outdoors.

APPLICATION:

SHAKE OR STIR WELL BEFORE USE

Apply preferably by spraying but brushing may be employed. The ideal application temperature is 15°C – 25°C.

STORAGE

Store in dry conditions away from other combustible materials, heat and direct sunlight. The product will gel at low temperatures but will revert to a normal consistency under normal working conditions.

USER BENEFITS:

PROTECTION

- Indoors 5 years minimum
- Covered Outdoors 5 years minimum
- Outdoors 2 years minimum

REMOVAL

If necessary, the film can be removed with common hydrocarbon solvent thinners, White Spirit or chlorinated hydrocarbon solvents

TYPICAL CHARACTERISTICS:

Appearance

Slightly brown liquid

Film Type

Firm wax film

Specific Gravity @ 15°C 0.860

Nominal Film Thickness 50 microns

Total Solids 35%

(Spray Application)

Flashpoint °C 35

Covering Capacity 7.0 sq m/litre

Drying Time 180 minutes

@ 20°C nominal



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk



PRODUCT DATA SHEET



HEALTH AND SAFETY:

Health and Safety Data Sheet 5628 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk