



# PRODUCT DATA SHEET



## PRODUCT NAME/VISCOSITIES:

### MOULD OIL 2437

Product No	5698
Issue No.	2
Issue Date	06/05/10

## DESCRIPTION:

A low viscosity mould oil formulated from a single base oil and an additive system ideal for effective mould oil release, primarily concrete and ceramic.

## APPLICATION:

Mould oil 2437 can be safely used with plastic, metal and rubber moulds and is particularly suitable for situations where an excellent finish is desired. Can be applied by brush, roller or spray.

## USER BENEFITS:

- Ease of application plus enhanced mould release and subsequent blemish free products are intrinsic attributes
- Readily biodegradable
- Suitable for a variety of moulds.

## TYPICAL CHARACTERISTICS:

Specific Gravity @ 15.4°C	0.8230
Kinematic Viscosity @ 40°C	4.2cSt
Flashpoint °C	120

## HEALTH AND SAFETY:

Health and Safety Data Sheet 5698 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

