

64000

HSS Circular Solid Die M DIN 223



Used for cutting external threads generally by hand when used in a metric die stock. There is no adjustment.

Discount Group	13
Material	HSS
Standard	DIN223
Packing Unit	All Sizes Packed in 1's

Surface Treatment	Bright
Tolerance	6g
Type	SOLID

Thread Ø x Pitch	Dec Inch Ø
------------------	------------

Outside Ø 20mm Width 5.0mm DIESTOCK 6941320.05	
---	--

M3 x 0.5	0.1181
M3.5 x 0.6	0.1377
M4 x 0.7	0.1574

Outside Ø 20mm Width 7.0mm DIESTOCK 6941320.07	
---	--

M5 x 0.8	0.1968
M6 x 1.0	0.2362

Outside Ø 25mm Width 9.0mm DIESTOCK 6941325.09	
---	--

M7 x 1.0	0.2755
M8 x 1.25	0.3149
M9 x 1.25	0.3543

Outside Ø 30mm Width 11.0mm DIESTOCK 6941330.011	
---	--

M10 x 1.5	0.3937
M11 x 1.5	0.4330

Thread Ø x Pitch	Dec Inch Ø
------------------	------------

Outside Ø 38mm Width 14.0mm DIESTOCK 6941338.014	
---	--

M12 x 1.75	0.4724
M14 x 2.0	0.5511

Outside Ø 45mm Width 18.0mm DIESTOCK 6941345.018	
---	--

M16 x 2.0	0.6299
M18 x 2.5	0.7086
M20 x 2.5	0.7874

Outside Ø 55mm Width 22.0mm DIESTOCK 6941355.022	
---	--

M22 x 2.5	0.8661
M24 x 3.0	0.9448