

64010

HSS Circular Solid Die MF DIN 223



Used for cutting external threads generally by hand when used in a metric die stock. There is no adjustment.

Discount Group	13
Material	HSS
Standard	DIN223
Packing Unit	All Sizes Packed in 1's

Surface Treatment	Bright
Tolerance	6g
Type	SOLID

Thread Ø x Pitch	Dec Inch Ø
A/F 20mm Width 5.0mm DIESTOCK 6941320.05	
M5 x 0.5	0.1968
A/F 20mm Width 7.0mm DIESTOCK 6941320.07	
M6 x 0.75	0.2362
A/F 25mm Width 9.0mm DIESTOCK 6941325.09	
M8 x 1.0	0.3149
A/F 30mm Width 11.0mm DIESTOCK 6941330.011	
M10 x 1.5	0.3937
M11 x 1.5	0.4330
A/F 38mm Width 10.0mm DIESTOCK 6941338.010	
M12 x 1.0	0.4724
M12 x 1.25	0.4724
M12 x 1.5	0.4724
M14 x 1.0	0.5511
M14 x 1.25	0.5511
M14 x 1.5	0.5511

Thread Ø x Pitch	Dec Inch Ø
Outside Ø 1.1/2" Width 1/2" DIESTOCK 694031 - 12	
M16 x 1.0	0.6299
M16 x 1.5	0.6299
M18 x 1.0	0.7086
M18 x 1.5	0.7086
M18 x 2.0	0.7086
M20 x 1.0	0.7874
M20 x 1.5	0.7874
M20 x 2.0	0.7874
A/F 55mm Width 16.0mm DIESTOCK 6941355.016	
M22 x 1.5	0.8661
M24 x 1.0	0.9448
M24 x 1.5	0.9448
M24 x 2.0	0.9448
A/F 65mm Width 18.0mm	
M27 x 1.5	1.0000
M27 x 2.0	1.0000
M27 x 1.0	1.0629
M30 x 1.0	1.1811
M30 x 1.5	1.1811
M30 x 2.0	1.1811